

25 YEAR COMMERCIAL WARRANTY  
AND LIFETIME RESIDENTIAL WARRANTY



# adore<sup>®</sup> Naturelle<sup>+</sup> Plus<sup>™</sup>

ENHANCED RESILIENT FLOORING FOR COMMERCIAL AND RESIDENTIAL ENVIRONMENTS



36 BEAUTIFUL DESIGNER-CURATED VISUALS • 10 VERSATILE NON-WOOD PLANK DESIGNS • NEW 24" SQUARE TILES  
22 MIL MICROCERAMIC™ WEAR LAYER • CLEANTECH™ EPA-CERTIFIED ANTIMICROBIAL SURFACTANT  
DURAMOND™ SCRATCH, SCUFF & STAIN RESISTANCE • ADA-COMPLIANT COMMERCIAL SLIP RESISTANCE  
ORTHOPHTHALATE FREE • 40% POST-INDUSTRIAL CONTENT • 100% RECYCLABLE

NAT-1741 ACHIEVE

NAT-1310 ACCLAIM

NAT-2031 ADVANCE

NAT-2032 ADMIRE

NAT-2033 ADVISE

NAT-2036 ADDRESS

NAT-2037 ADAPT

NAT-2042 ADMIT

NAT-2044 ACCRUE

NAT-2051 ADORN

NAT-3151 APPEAL

NAT-3301 ASPIRE

NAT-3302 AGREE

NAT-3303 ACCEPT

NAT-4100 APPOINT

NAT-4101 APPLAUD

NAT-4302 ATTRACT

NAT-4500 ADRIFT

## SPECIFICATIONS

ASTM F1700-96, CLASS III, TYPE B  
HETEROGENEOUS VINYL FLOORING

### FIRE

ASTM E84 75 OR LESS  
ASTM E648 CLASS 1

### SMOKE

ASTM E662 PASS

### RESIDUAL INDENTATION

ASTM F1914 ≤ 8%

### STATIC LOAD LIMIT

ASTM F970 1,500 P.S.I.

### FLEXIBILITY

ASTM F137 PASS

### HARDNESS-DUROMETER

SHORE A 90±5

### DIMENSIONAL STABILITY

ASTM E2199 PASS

### SLIP RESISTANCE

ASTM C1028 MEETS ADA/OSHA  
REQUIREMENT

### COLOR FASTNESS

ISO 105-B02 ≥ GRADE 6

### RADIANT HEAT SUITABILITY

COMPATIBLE UP TO 85°F

### CHAIR CASTOR SUITABILITY

PHILLIPS ROLL 5 RATING  
CHAIR TEST @ 25,000 CYCLES

### VOC EMISSIONS

FLOORSORE® CERTIFIED

### CHEMICAL RESISTANCE

ASTM F925 EXCELLENT

### NOISE ATTENUATION

ASTM E2179 ΔIIC 10  
ASTM E492 IIC 48  
ASTM E90 STC 49

NAT-631 ALLY

NAT-632 ALLOW

NAT-634 ALLURE

NAT-701 ACCENT

NAT-703 ADOPT

NAT-731 ACCESS

NAT-741 ASCEND

NAT-742 ABOUND

NAT-743 ADVENT

NAT-903 ACQUIRE

NAT-906 ANCHOR

NAT-904 ANNEX

NAT-665 AMPLIFY

NAT-661 AFFIRM

NAT-603 ASTOUND

NAT-604 ATTAIN

NAT-652 ASSURE

NAT-651 AFFORD

## PRODUCT DIMENSIONS

### WIDE PLANKS (NAT-1741 ONLY)

22 MIL/0.55MM WEAR LAYER  
7.2" X 37.4" X 0.12" (NOM.)  
19 PLANKS PER CARTON  
35.76 FT<sup>2</sup> PER CARTON  
37.7 LBS PER CARTON

### LONG PLANKS

22 MIL/0.55MM WEAR LAYER  
7.0" X 48.0" X 0.12" (NOM.)  
15 PLANKS PER CARTON  
35.00 FT<sup>2</sup> PER CARTON  
36.9 LBS PER CARTON

### RECTANGULAR TILES

22 MIL/0.55MM WEAR LAYER  
12.3" X 24.5" X 0.12" (NOM.)  
18 TILES PER CARTON  
38.16 FT<sup>2</sup> PER CARTON  
40.2 LBS PER CARTON

### XL SQUARE TILES

22 MIL/0.55MM WEAR LAYER  
23.6" X 23.6" X 0.12" (NOM.)  
9 TILES PER CARTON  
34.87 FT<sup>2</sup> PER CARTON  
36.8 LBS PER CARTON

adore®

5 dubon court, farmingdale, ny 11735  
(877) 359-5095 | adorefloors.com