



D5M-5102
DIMENSION




D5M-5103
ECHELON




D5M-5105
PROCLAIM




D5M-5107
DEGREE




D5M-5112
FOREMOST



D5M-5114
FORTITUDE



D5M-5411
HERALD



D5M-5601
MAGNITUDE




D5M-5602
PREMIER




D5M-5603
PROPORTION




D5M-5612
RESILIENCE




D5M-5719
RESISTANCE



D5M-5780
RESONATE



D5M-5802
STRATUM



D5M-5805
SUBSTANTIAL

SPECIFICATIONS

ASTM F1700-96, CLASS III, TYPE B HETEROGENEOUS VINYL FLOORING

13/64" (5.0MM) OVERALL
30 MIL (0.75MM) WEAR LAYER
9.0" X 60" PLANK DIMENSIONS
8 PLANKS / CARTON
30 SQ. FT. / CARTON
51.2 LBS. / CARTON

FIRE

ASTM E84 75 OR LESS
ASTM E648 CLASS 1

SMOKE

ASTM E662 PASS

RESIDUAL INDENTATION

ASTM F1914 ≤ 8%

STATIC LOAD LIMIT

ASTM F970 1,500 P.S.I.

FLEXIBILITY

ASTM F137 PASS

HARDNESS-DUROMETER

SHORE A 90±5

DIMENSIONAL STABILITY

ASTM E2199 PASS

SLIP RESISTANCE

ASTM C1028 MEETS ADA/OSHA
REQUIREMENT

COLOR FASTNESS

ISO 105-B02 ≥ GRADE 6

RADIANT HEAT SUITABILITY

COMPATIBLE UP TO 85°F

CHAIR CASTOR SUITABILITY

PHILLIPS ROLL 5 RATING
CHAIR TEST @ 25,000 CYCLES

VOC EMISSIONS

FLOORSORE® CERTIFIED

CHEMICAL RESISTANCE

ASTM F925 EXCELLENT

NOISE ATTENUATION

ASTM E2179 ΔIIC 23
ASTM E492 IIC 57
ASTM E90 STC 50

adore®

100 CROSSWAYS PARK DR W, SUITE 315
WOODBURY, NY 11797 | (877) 359-5095
SAMPLES@ADOREFLOORS.COM

adore[®] Decoria



5MM COMMERCIAL-GRADE 30MIL ACOUSTIC LUXURY VINYL PLANKS

