

1. IDENTIFICATION		2. DOT INFORMATION	
Supplier:	Adore Floors	Shipping Name:	Not Classified
Address:	100 Crossways Park Dr W, Ste 315 Woodbury, NY 11797	Hazard Class:	N/A
Main Phone:	(877) 359-5095	UN/NA #:	N/A
Direct Phone:	(631) 843-0900	3. HMIS	
Emergency:	(877) 779-2454 [M-F 9am-5pm EDT]	Health:	0
Website:	https://adorefloors.com	Flammability:	1
Email:	info@adorefloors.com	Physical Hazard:	0
Product:	Luxury Vinyl Tile	Personal Protection:	0
Description:	Floating and Gluedown Vinyl Floor Covering	4. PRODUCT COMPOSITION	
Brands:	Naturelle+Plus, ProjectFlor, ProjectFlor Elite, Regent Monarch X, Regent Sovereign, Decoria Contact	This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does NOT contain asbestos.	

5. HAZARDOUS INGREDIENTS					
Chemical Identity	C.A.S.	%	OSHA PEL	ACGIH TLV	Ingredient Information
PVC	9002-86-2	32	N/A	N/A	These vinyl flooring products are produced for residential and commercial (architectural) marketplace use. They come in a wide variety of aesthetic designs, styles, colors, surface finishes, and sizes.
CaCO ₃	471-34-1	58	N/A	N/A	
DOTP	117-81-7	9	N/A	N/A	
Proprietary	N/A	1	N/A	N/A	
Miscellaneous Information					
Each of these products is classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200(c). They are formed to a specific shape or design during manufacture, have end use functions dependent upon their shape or design, and do not release any hazardous chemical under normal conditions of use.					

6. PHYSICAL DATA		7. FIRE & EXPLOSION HAZARD DATA		
Appearance:	Solid Tiles	Flash Point:	N/A	
Boiling Point:	N/A	Flammable Range	LEL:	N/A
Vapor Pressure:	N/A		UEL:	N/A
Vapor Density:	N/A	Extinguishing Media:	Water spray, CO ₂ , foam, dry chemical extinguishing agent, determined appropriate for surrounding environment	
% Volatile by Weight:	N/A	Special Procedures:	Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus.	
Evaporation Rate:	N/A	Unusual Fire Hazards:	None	
Solubility in Water:	Negligible			
Specific Gravity:	1.5 - 2.4			
pH:	N/A			

8. HEALTH HAZARD DATA			9. REACTIVITY DATA	
Likely Route(s) of Exposure	Exposure Symptoms	First Aid Procedures	Stability:	N/A
Skin & Eyes:	Possible mild irritation	Flush with water, like any non-hazardous material	Incompatibility:	N/A
Inhalation:	Beware of adhesive inhalation precautions	Not expected, but seek fresh air and medical assistance in case of adverse reaction.	Hazardous Polymerization:	N/A
Ingestion:	Small amounts should cause no injury	Seek medical assistance if a considerable amount is ingested	Hazardous Decomposition:	Caution (See Below)
OSHA Regulated:	No	This product is a solid consumer good, relatively non-toxic, presents no known hazard to people	Thermal decomposition may release: CO, CO ₂ , aliphatic aldehydes, terpenes, and polycyclic aromatic hydrocarbons.	

10. SPILL OR LEAK PROCEDURES		11. SAFE HANDLING & USE		12. SPECIAL PRECAUTIONS	
Steps to be taken if material spills:	N/A	Ventilation:	N/A	Handling & Storage Precautions:	None
Always dispose in accordance with Federal, State and Local Waste Disposal Regulations		Respiratory:	N/A	Other Precautions:	See Below
		Skin & Eye:	N/A	Product must be stored in temperate, dry location away from any fire or open flame sources	
		Other Precautions:	N/A		

13. WARNING
FOR PREVIOUSLY INSTALLED FLOOR COVERINGS: DO NOT SAND, DRY SCRAPE, BEADBLAST, OR MECHANICALLY PULVERIZE EXISTING RESILIENT FLOORING, BACKING OR LINING FELT. THESE PRODUCTS MAY CONTAIN EITHER ASBESTOS FIBERS OR CRYSTALLINE SILICA. POSSIBLE CANCER AND RESPIRATORY TRACT HAZARD BY INHALATION. AVOID CREATING DUST. SMOKING BY INDIVIDUALS WHO HAVE BEEN EXPOSED TO ASBESTOS FIBERS GREATLY INCREASES THE RISK OF SERIOUS BODILY HARM. RFCI'S (Resilient Floor Covering Institute) RECOMMENDED WORK PRACTICES FOR REMOVAL OF RESILIENT FLOOR COVERINGS ARE A DEFINED SET OF INSTRUCTIONS ADDRESSED TO THE TASK OF REMOVING ALL RESILIENT FLOOR COVERING STRUCTURES.

14. NOTICE
Various government agencies have regulations governing the removal of in-place asbestos-containing materials. If you contemplate the removal of a resilient floor covering structure that contains (or is assumed to contain) asbestos, you should determine whether such regulations apply. The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user decides the adequacy of the safety procedures employed during the use of this product.